

Brain erd/Baxter 7804 Industrial Park Road PO Box 2720 Baxter, MN 56425-2720



WidsethSmithNolting.com

UNSEWERED AREAS ENVIRONMENTAL ASSESSMENT

Reviewed with City Council at Special Meeting on July 25, 2019 No Formal Acceptance by City Council

Prepared for City of Baxter

WSN No. 0102B0412.000

Engineering Architecture Surveying Environmental

UNSEWERED AREAS ENVIRONMENTAL ASSESSMENT

Pre	pai	red	for
City	of	Ba	xter

WSN No. 0102B0384.000

I hereby certify that this report was prepared by me or under my direct supervision and that I am a duly Licensed Professional Geologist under the laws of the State of Minnesota.

Brian Ross License Number Date
Professional Geologist

UNSEWERED AREAS ENVIRONMENTAL ASSESSMENT

TABLE OF CONTENTS

Certification Sheet	CS
Table of Contents	TC
Statement of Purpose	1
Background	1
Site Assessment	1
Discussion	3
Conclusions and Recommendations	4
Limitations	5

LIST OF FIGURES

Figure 1 – Site Location Map

Figure 2 – Lugo Property Site Map

Figure 3 – Katzenberger Site Map

Figure 4 – Bolt Site Map

TABLES

Table 1 – PID Results

Table 2 – Groundwater Analytical Results

Table 3 – Water Quality Readings

ATTACHMENTS

Attachment A – Field Methods and Procedures

Attachment B – Laboratory Analytical Data

Attachment C - Soil Boring Logs

STATEMENT OF PURPOSE

This letter presents the results of a Unsewered Areas Environmental Assessment completed by Widseth Smith Nolting (WSN) for the City of Baxter. The sampling was requested to evaluate potential for groundwater and/or surface water impacts caused by individual sewer treatment systems (ISTSs).

BACKGROUND

The City of Baxter is looking at extending city sewer and water services to areas of town that currently have private domestic water wells and ISTSs. In order to help make this decision, the City of Baxter is requesting assistance to obtain data on the potential impacts to groundwater and surface water resources in the City's unsewered areas from the ISTSs. The data collected from this assessment will be used to aid the City when making the decision about whether or not the City will move ahead with installing municipal sewer and water systems in the unsewered areas.

SITE ASSESSMENT

On May 9, 2019, a WSN field technician mobilized to four separate residences located in the City of Baxter. The Lugo residence and Katzenberger residence which are located in the unsewered area of Lynndale Drive. The Bolt residence and another residence located were in the unsewered area of Scenic River Drive in Baxter, MN. A subcontractor's drilling equipment malfunction resulted in no samples being obtained at the other residence along Scenic River Drive. Two soil borings were advanced on the downgradient side of each ISTS on each property with one soil boring being located adjacent to the ISTS drainfield and the other boring being located approximately 50 to 60 feet downgradient of the drain field. The soil boring locations were chosen with the goal of trying to assess if the ISTSs are affecting the shallow groundwater. A groundwater sample was collected from each soil boring for the analysis of total coliforms, nitrate, and chloride. Water quality parameters were also collected from the groundwater purged from each soil boring for temperature, specific conductance, pH, and ORP using a Hydrolab Quanta water quality meter. The location of the sites is illustrated on Figure 1. Each site and the

sample locations are illustrated on Figures 2 through 4.

Two soil borings were advanced at the Lugo residence located on Lynndale Drive in Baxter, MN. The first soil boring (Lugo #1) was advanced on the south side of the septic system which is located on the north side of the house. The second soil boring (Lugo #2) was advanced to the southwest of Lugo #1 on the west side of the house. Both boring locations were advanced at locations that were downgradient of the septic drain field. Soil borings Lugo #1 and Lugo #2 were advanced to a depth of 8 feet below land surface (BLS). Static water was measured in Lugo #1 at a depth of 1.8 feet BLS while the static water level in Lugo #2 was measured at a depth of 1.1 feet BLS. Soils encountered in Lugo #1 and Lugo #2 were a fill material consisting of approximately a foot of silty sand with the top four inches being highly organic in nature. Underneath the fill material was a fine-grained sand to a depth of 8 feet BLS. A groundwater sample was collected from each soil boring and analyzed for total coliforms, nitrate, and chloride.

Two soil borings were completed at the Katzenberger residence located on Lynndale Lane in Baxter, MN. The first soil boring (Katzenberger #1) was advanced just south of the septic drain field located southeast of the house. The second soil boring (Katzenberger #2) was advanced directly to the west between Red Sand Lake and the septic drain field. Soil borings were advanced at locations that were downgradient of the septic drain field. Soil borings Katzenberger #1 and Katzenberger #2 were both advanced to a depth of 12 feet BLS. The static water level was measured in Katzenberger #1 at a depth of 8.7 feet BLS and 7.0 feet BLS in Katzenberger #2. Soils encountered in Katzenberger #1 and Katzenberger #2 were a fill material consisting of a dark brown silty sand to a depth of approximately 1 foot BLS. Underneath the fill material was a red/tan fine sand to a depth of four feet BLS underlain by a tan fine sand with trace gravel to a depth of 12 feet BLS. One groundwater sample was collected from each boring location and analyzed for total coliforms, nitrate, and chloride.

Two soil borings were completed at the Bolt residence located on Scenic River Drive in Baxter, MN. The first soil boring (Bolt #1) was advanced just south of the septic drain field located southeast of the house. The second soil boring (Bolt #2) was advanced directly to the east of the septic drain field. Soil borings were advanced at locations that were downgradient of the septic drain field. Soil borings Bolt #1 and Bolt #2 were both advanced to a depth of 24 feet BLS. The static water level was measured in Bolt #1 at a depth of 18.3 feet BLS and 23.7 feet BLS in Bolt

#2. Soils encountered in Bolt #1 and Bolt #2 consisted a fill material of dark brown silty sand to a depth of approximately 1 foot BLS. Underneath the fill material was a brown fine sand to a depth of seven feet BLS underlain by a tan fine to medium coarse grained sand with trace gravel to a depth of 24 feet BLS. One groundwater sample was collected from each boring location and analyzed for total coliforms, nitrate, and chloride

The soil borings were advanced using an AMS 9130-VTR-D power probe. During advancement of the soil borings, soil samples were collected every 24 inches for field organic vapor screening using a MiniRae Photoionization Detector (PID) equipped with a 10.6 eV lamp. Samples were screened for organic vapors by placing a portion of the sample in a sealed bag, breaking the sample apart to allow vapors to escape and measuring a reading by inserting the PID meter into the bag. The field organic vapor screening results are presented in Table 1. Soil samples were also inspected for visual and olfactory indications of contamination (i.e., discoloration and odors). Once the soil boring was completed a temporary screen was installed and a check ball with tubing was used to purge groundwater from the soil boring. One groundwater sample was collected for each soil boring and analyzed for total coliforms, nitrate, and chloride. Groundwater samples were collected in laboratory-supplied containers, placed on ice, and submitted for laboratory analysis following proper chain-of-custody procedures. Field methods and procedures are described in further detail in Attachment A.

DISCUSSION

Table 1 presents the field organic screening results. PID results ranged from 0.4 ppm to 1.8 ppm and indicates that no elevated organic vapors were encountered during this assessment. No visual signs of contamination were observed in the field during drilling activities.

Table 2 presents the groundwater analytical results from the assessment. Analytical results show that total coliforms were present in Lugo #1 at 100 CFU/100 mL and Katzenberger #2 at 300 CFU/100mL. Total coliforms were not reported in Lugo #2, Katzenberger #1, Bolt #1 and Bolt #2 above the laboratory detection limit. Nitrate was reported in groundwater samples collected from Lugo #1 and Katzenberger #1 at concentrations of 49.6 ppm and 31.1 ppm respectively. Naturally occurring background levels of nitrate concentrations were observed during the assessment ranging from 0.11 ppm to 1.6 ppm. The health risk limit (HRL)

established by the Minnesota Department of Health for nitrate in drinking water is 10 ppm. Chloride was reported in groundwater samples above background levels in Lugo #1 and Katzenberger #1 at concentrations of 118 ppm and 198 ppm. Background levels of chloride were reported during this investigation ranging from 20.8 ppm to 39.7 ppm.

Table 3 presents the field water quality readings collected from each soil boring. Parameters collected were temperature, specific conductance, dissolved oxygen, pH, and ORP.

The results for total coliforms, nitrate, and chloride indicate that the groundwater downgradient of the ISTS on the Lugo property and Katzenberger property has been impacted from the use of ISTSs. The detections of chloride at concentrations of two or more times above background levels in Lugo #1 and Katzenberger #1 is most likely due to the presence of septic related contamination. It should also be noted that elevated water quality readings were also reported in Lugo #1 and Katzenberger #1 for specific conductance which can be an indicator of groundwater contamination because higher specific conductance readings is an indication that there are more chemicals dissolved in the water. As stated above, nitrate was reported in Lugo #1 and Katzenberger #1 at concentrations above the HRL of 10 ppm. Groundwater flow in the Lynndale area is believed to be to the west or towards Red Sand Lake and groundwater flow in the River Scenic Drive area is most likely to the east or southeast towards the Mississippi River. Results reported from the two soil borings advanced on the Bolt property did not appear to be significantly affected from the ISTS as no total coliforms were detected and detections of nitrate appear to be naturally occurring background levels. The chloride concentrations are above background levels and it maybe that groundwater is flowing a different direction than anticipated.

CONCLUSIONS AND RECOMMENDATIONS

WSN was contracted by the City to assess four residential properties, two in the Lynndale Lane area and two in the Scenic River/Forestview Drives area of Baxter, for groundwater contamination associated with their onsite sewage treatment systems. Subcontractor drilling equipment problems prevented completing the assessment at one of the properties along Scenic River Drive.

The results of the assessment indicated significant groundwater contamination near two of the


three systems. High levels of nitrate and total coliform bacteria and elevated levels of chloride were found in the groundwater near the sewage treatment systems and to a lesser extent downgradient of the systems. The high nitrate levels ranged from 31.1 milligram per liter (mg/L) to 49.6 mg/L, which are three and four times the drinking water limit of 10 mg/L. The detections of total coliform bacteria ranged from 100 to 300 colony forming units with the drinking water limit being zero. The third system had some indications of contamination in the form of elevated chloride levels.


Because of the limited nature of the assessment, it is uncertain where the downgradient sampling point was located in relation to the highest level of contamination in the groundwater plume from the system. In addition, the detection of nitrates and total coliforms are indicators of that the systems are affecting groundwater; analyzing for the many other contaminants possibly present such as pharmaceuticals, solvents, and chemical elements would likely indicate some of those contaminants are present as well.


WSN recommends additional sampling be completed, to gather more data related to groundwater contamination from ISTSs, on at least two more properties in the Scenic River Drive area of Baxter.


LIMITATIONS


WSN completed this assessment following standard field and laboratory methods of the industry. The conclusions represent the opinions of WSN's staff, in accordance with currently accepted geologic, hydrogeologic, and environmental practices at this time and location. This assessment was completed only for septic related contamination near ISTSs. The presence or absence of contamination can only be reported at the location of each sample location completed as part of this assessment. No other assurances are applied or assumed.














Table 1
Unsewered Areas Environmental Assessment
Baxter, MN
PID Results (ppm)

Depth	Lugo #1	Lugo #2	Katzenberger #1	Katzenberger #2	Bolt #1	Bolt #2
0-2	0.4	1.1	0.4	0.9	1.3	1
2-4	1.1	1.3	0.8	1.1	1.1	1.3
4-6	1.2	1.4	1.1	1.7	1.2	0.7
6-8	1.2	1.5	1.4	1.6	1.4	1
8-10			1.6	1.4	1.6	1.3
10-12			1.2	1.3	1.7	1.2
12-14					1.8	1.2
14-16					1.7	1.7
16-18					1.5	0.9
18-20					1.6	1.8
20-22					1.3	1.2
22-24					1.3	1.1

Table 2
Unsewered Areas Environmental Assessment
Baxter, MN

Groundwater Analytical Results

	Units	Lugo #1	Lugo #2	Katzenberger #1	Katzenberger #2	Bolt #1	Bolt #2
Date Sampled		5/9/2019	5/9/2019	5/9/2019	5/9/2019	5/9/2019	5/9/2019
Total Coliforms	CFU/100mL	100	<100	<100	300	<100	<100
Nitrate	mg/L	49.6	0.12	31.1	1.6	0.11	<0.10
Chloride	mg/L	118	27.6	198	20.8	34.7	39.7

CFU/100mL = colony forming units per 100 mL

mg/L = milligrams per liter = parts per million (PPM)


Table 3

Unsewered Area Environmental Assessment Baxter, MN

Water Quality Readings

	Units	Lugo #1	Lugo #2	Katzenberger #1	Kaztenberger #2	Bolt #1	Bolt #2
Temp	°F	46.3	43.2	45.2	43.8	50.2	51.6
Specific Conductance	μS/cm	945	220	1080	162	311	477
Dissloved Oxygen	mg/l	6.76	6.69	6.76	6.30	6.09	4.32
рН	units	6.29	6.74	6.87	7.02	7.12	7.56
ORP	mv	291	77	168	180	161	209

μS/cm = micro-Siemens per centimeter



ATTACHMENT A Field Methods and Procedures

FIELD METHODS AND PROCEDURES

1.0 SOIL SAMPLING

Soil samples were collected using Macro-Core Samplers, which provide continuous sample collection downward using 48"long X 1.5" diameter tool and retains the sample in a PETG (clear plastic) liner tube. This allows for continuous sampling the entire length of the Geoprobe bore hole. After collection, the sample tubes are removed from the macro-core barrel, the liner tube is cut open and grab samples are collected from the liner tube for field analysis of organic vapors. In addition, a grab sample is obtained for laboratory analyses following MPCA Fact Sheet 3.22.

2.0 DECONTAMINATION OF DRILLING EQUIPMENT

The geoprobe and associated tools were steam cleaned prior to the start of any project work. The geoprobe sampler was cleaned between samples to minimize cross-contamination and the geoprobe sample tube inserts are disposable and a new insert is used for each new sample. The cleaning procedure for the sampler consisted of scrubbing the sampler with a brush in a soap and water solution followed by a tap water rinse. The soap and water were changed regularly during the sampling. Fluids used for onsite cleaning of the split barrel sampler and drilling equipment were disposed on the site.

3.0 SOIL CLASSIFICATION

As the samples were obtained in the field, they were visually and manually classified by a WSN representative in accordance with ASTM: D2488-93. Representative portions of the samples were then returned to WSN's office in the event there is need for further examination and verification of the field classification. The classification of soil boring samples, soil boring depths, identification of the various strata, the soil consistency, water level information, and pertinent information regarding the method of maintaining and advancing the drill holes are presented on boring logs. Charts describing the soil classification procedure, the descriptive terminology, and symbols used on the boring logs are included with the logs.

4.0 SOIL ORGANIC VAPOR MONITORING

Soil samples were screened for organic vapors with a Mini Rae 2000 photoionization detector (PID) equipped with a 10.6 eV lamp and calibrated for a direct equivalent reading of parts per million. Organic vapor concentrations were recorded using the headspace method. During cold weather, PID headspace readings were taken in a heated space.

6.0 GROUNDWATER LEVEL MEASUREMENTS

Groundwater level measurements were obtained using an electronic measuring instrument. The instrument is equipped with a probe that emits an electric signal when in contact with water. Measurements are obtained by lowering the probe into the boring or well and recording the depth of the probe when the electric signal indicates contact with water. Measurements are referenced to the top of ground surface or the top of the monitoring well casing (if installed) and recorded to the nearest 0.01 feet.

The manufacturer's reported accuracy for the instrument is 0.04 feet.

7.0 GROUNDWATER SAMPLING FOR CHEMICAL ANALYSIS

Groundwater samples from the geoprobes were obtained using disposable Teflon tubing and a check valve. Insufficient water was present to use a small electric pump or bailer. New tubing is used for each sample. Trip blanks of distilled water are also collected at the site.

Groundwater samples are collected in clean, laboratory supplied, glass containers affixed with labels listing the type of analysis and sample identification. Appropriate preservation techniques are used for those samples as required. The sample bottles are appropriately labeled with the job number, location number, date sampled, and initials of the individual sampler. A chain-of-custody form is completed and shipped with the samples to the laboratory. Upon arrival at the laboratory, the samples are checked in and signed over to the appropriate laboratory personnel. At that time, a copy of the chain-of-custody form is retained and returned to the project manager.

ATTACHMENT B Laboratory Analytical Data



May 17, 2019

Mr. Brian Ross Widseth Smith Nolting 7804 Industrial Park Road Box 2730 Baxter, MN 56425

RE: Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Dear Mr. Ross:

Enclosed are the analytical results for sample(s) received by the laboratory on May 10, 2019. The results relate only to the samples included in this report. Results reported herein conform to the most current, applicable TNI/NELAC standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Oyeyemi Odujole oyeyemi.odujole@pacelabs.com (612)607-6402 Project Manager

Enclosures







CERTIFICATIONS

Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Minnesota Certification IDs

1700 Elm Street SE, Minneapolis, MN 55414-2485

A2LA Certification #: 2926.01 Alabama Certification #: 40770

Alaska Contaminated Sites Certification #: 17-009

Alaska DW Certification #: MN00064 Arizona Certification #: AZ0014 Arkansas DW Certification #: MN00064 Arkansas WW Certification #: 88-0680 California Certification #: 2929 CNMI Saipan Certification #: MP0003 Colorado Certification #: MN00064

Connecticut Certification #: PH-0256 EPA Region 8+Wyoming DW Certification #: via MN 027-

053-137

Florida Certification #: E87605 Georgia Certification #: 959

Guam EPA Certification #: MN00064
Hawaii Certification #: MN00064
Idaho Certification #: MN00064
Illinois Certification #: 200011
Indiana Certification #: C-MN-01
Iowa Certification #: 368
Kansas Certification #: E-10167
Kentucky DW Certification #: 90062
Kentucky WW Certification #: 90062
Louisiana DEQ Certification #: 03086

Louisiana DW Certification #: MN00064 Maine Certification #: MN00064 Maryland Certification #: 322

Massachusetts Certification #: M-MN064

Michigan Certification #: 9909

Minnesota Certification #: 027-053-137

Minnesota Dept of Ag Certification #: via MN 027-053-137


Minnesota Petrofund Certification #: 1240
Mississippi Certification #: MN00064
Missouri Certification #: 10100
Montana Certification #: CERT0092
Nebraska Certification #: NE-OS-18-06
Nevada Certification #: MN00064
New Hampshire Certification #: 2081
New Jersey Certification #: MN002
New York Certification #: 11647

North Carolina DW Certification #: 27700 North Carolina WW Certification #: 530 North Dakota Certification #: R-036 Ohio DW Certification #: 41244 Ohio VAP Certification #: CL101 Oklahoma Certification #: 9507

Oregon Primary Certification #: MN300001
Oregon Secondary Certification #: MN200001
Pennsylvania Certification #: 68-00563
Puerto Rico Certification #: MN00064
South Carolina Certification #:74003001
Tennessee Certification #: TN02818
Texas Certification #: T104704192
Utah Certification #: WN00064
Vermont Certification #: VT-027053137
Virginia Certification #: 460163
Washington Certification #: C486
West Virginia DEP Certification #: 382
West Virginia DW Certification #: 9952 C

Wyoming UST Certification #: via A2LA 2926.01

Wisconsin Certification #: 999407970





SAMPLE SUMMARY

Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Lab ID	Sample ID	Matrix	Date Collected	Date Received
10474250001	Lugo #1	Water	05/09/19 09:34	05/10/19 09:30
10474250002	Lugo #2	Water	05/09/19 10:15	05/10/19 09:30
10474250003	Katzenberger #1	Water	05/09/19 11:11	05/10/19 09:30
10474250004	Katzenberger #2	Water	05/09/19 11:47	05/10/19 09:30
10474250005	Bolt #1	Water	05/09/19 13:54	05/10/19 09:30
10474250006	Bolt #2	Water	05/09/19 14:55	05/10/19 09:30

(612)607-1700



SAMPLE ANALYTE COUNT

Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Lab ID	Sample ID	Method	Analysts	Analytes Reported
10474250001	 Lugo #1	SM 9222B	JFP	1
		EPA 353.2	JFP	1
		SM 4500-CI E	KEO	1
10474250002	Lugo #2	SM 9222B	JFP	1
		EPA 353.2	JFP	1
		SM 4500-CI E	KEO	1
10474250003	Katzenberger #1	SM 9222B	JFP	1
		EPA 353.2	JFP	1
		SM 4500-CI E	KEO	1
10474250004	Katzenberger #2	SM 9222B	JFP	1
		EPA 353.2	JFP	1
		SM 4500-CI E	KEO	1
10474250005	Bolt #1	SM 9222B	JFP	1
		EPA 353.2	JFP	1
		SM 4500-CI E	KEO	1
10474250006	Bolt #2	SM 9222B	JFP	1
		EPA 353.2	JFP	1
		SM 4500-CI E	KEO	1



Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

Sample: Lugo #1	Lab ID: 10	474250001 C	ollected: 05/09/1	19 09:34	Received: 05	/10/19 09:30 N	Matrix: Water	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
MBIO 9222B Total Coliform MF	Analytical Me	thod: SM 9222B	Preparation Me	thod: SN	M 9222B			
Total Coliforms	100	CFU/100 mL	100	100	05/10/19 10:14	05/11/19 10:14		H1
353.2 Nitrate + Nitrite	Analytical Me	thod: EPA 353.2						
Nitrate as N	49.6	mg/L	5.0	50		05/10/19 12:12	14797-55-8	
SM4500CI-E Chloride	Analytical Me	thod: SM 4500-0	CIE					
Chloride	118	mg/L	20.0	10		05/13/19 09:44	16887-00-6	M6






Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

Sample: Lugo #2	Lab ID: 10	474250002 Co	ollected: 05/09/1	9 10:15	Received: 05	5/10/19 09:30 N	Matrix: Water	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
MBIO 9222B Total Coliform MF	Analytical Me	thod: SM 9222B	Preparation Met	thod: SN	И 9222B			
Total Coliforms	<100	CFU/100 mL	100	100	05/10/19 10:14	05/11/19 10:14		
353.2 Nitrate + Nitrite	Analytical Me	thod: EPA 353.2						
Nitrate as N	0.12	mg/L	0.10	1		05/10/19 11:49	14797-55-8	FS
SM4500CI-E Chloride	Analytical Me	thod: SM 4500-C	il E					
Chloride	27.6	mg/L	4.0	2		05/13/19 09:24	16887-00-6	






Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

Sample: Katzenberger #1	Lab ID: 10	474250003 Co	ollected: 05/09/1	9 11:11	Received: 05	5/10/19 09:30 I	Matrix: Water	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
MBIO 9222B Total Coliform MF	Analytical Me	thod: SM 9222B	Preparation Met	thod: SN	/I 9222B			
Total Coliforms	<100	CFU/100 mL	100	100	05/10/19 10:14	05/11/19 10:14		
353.2 Nitrate + Nitrite	Analytical Me	thod: EPA 353.2						
Nitrate as N	31.1	mg/L	5.0	50		05/10/19 12:13	14797-55-8	
SM4500CI-E Chloride	Analytical Me	thod: SM 4500-C	CI E					
Chloride	198	mg/L	20.0	10		05/13/19 09:44	16887-00-6	





Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

Sample: Katzenberger #2	Lab ID: 10	474250004 Co	ollected: 05/09/1	9 11:47	Received: 05	5/10/19 09:30 M	/latrix: Water	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
MBIO 9222B Total Coliform MF	Analytical Me	ethod: SM 9222B	Preparation Met	hod: SN	И 9222B			
Total Coliforms	300	CFU/100 mL	100	100	05/10/19 10:14	05/11/19 10:14		
353.2 Nitrate + Nitrite	Analytical Me	ethod: EPA 353.2						
Nitrate as N	1.6	mg/L	0.10	1		05/10/19 11:52	14797-55-8	FS
SM4500CI-E Chloride	Analytical Me	ethod: SM 4500-C	I E					
Chloride	20.8	mg/L	2.0	1		05/13/19 09:03	16887-00-6	



Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

Sample: Bolt #1	Lab ID: 10	474250005 Co	ollected: 05/09/1	19 13:54	Received: 05	5/10/19 09:30 M	latrix: Water	
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual
MBIO 9222B Total Coliform MF	Analytical Me	thod: SM 9222B	Preparation Me	thod: SN	И 9222B			
Total Coliforms	<100	CFU/100 mL	100	100	05/10/19 10:14	05/11/19 10:14		
353.2 Nitrate + Nitrite	Analytical Me	thod: EPA 353.2						
Nitrate as N	0.11	mg/L	0.10	1		05/10/19 11:53	14797-55-8	FS
SM4500CI-E Chloride	Analytical Me	thod: SM 4500-C	I E					
Chloride	34.7	mg/L	4.0	2		05/13/19 09:24	16887-00-6	






Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

Sample: Bolt #2	Lab ID: 104	74250006 Co	ollected: 05/09/1	19 14:55	Received: 05	5/10/19 09:30 M	Matrix: Water		
Parameters	Results	Units	Report Limit	DF	Prepared	Analyzed	CAS No.	Qual	
MBIO 9222B Total Coliform MF	Analytical Method: SM 9222B Preparation Method: SM 9222B								
Total Coliforms	<100	CFU/100 mL	100	100	05/10/19 10:14	05/11/19 10:14			
353.2 Nitrate + Nitrite	Analytical Met	hod: EPA 353.2							
Nitrate as N	ND	mg/L	0.10	1		05/10/19 11:54	14797-55-8	FS	
SM4500CI-E Chloride	Analytical Method: SM 4500-CI E								
Chloride	39.7	mg/L	4.0	2		05/13/19 09:31	16887-00-6		





QUALITY CONTROL DATA

Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

QC Batch: 605113 Analysis Method: SM 9222B

QC Batch Method: SM 9222B Analysis Description: 9222B MBIO Total Coliforms
Associated Lab Samples: 10474250001, 10474250002, 10474250003, 10474250004, 10474250005, 10474250006

METHOD BLANK: 3271225 Matrix: Water


Associated Lab Samples: 10474250001, 10474250002, 10474250003, 10474250004, 10474250005, 10474250006

Blank Reporting

Parameter Units Result Limit Analyzed Qualifiers

Total Coliforms CFU/100 mL <1 1.0 05/11/19 10:14

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.





QUALITY CONTROL DATA

Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

QC Batch: 605133 Analysis Method: EPA 353.2

QC Batch Method: EPA 353.2 Analysis Description: 353.2 Nitrate + Nitrite, preserved Associated Lab Samples: 10474250001, 10474250002, 10474250003, 10474250004, 10474250005, 10474250006

METHOD BLANK: 3271296 Matrix: Water

Associated Lab Samples: 10474250001, 10474250002, 10474250003, 10474250004, 10474250005, 10474250006

Blank Reporting

ParameterUnitsResultLimitAnalyzedQualifiersNitrate as Nmg/LND0.1005/10/19 11:55FS

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

(612)607-1700



QUALITY CONTROL DATA

Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

QC Batch: 605370 Analysis Method: SM 4500-CI E

QC Batch Method: SM 4500-Cl E Analysis Description: SM4500Cl-E Chloride

Associated Lab Samples: 10474250001, 10474250002, 10474250003, 10474250004, 10474250005, 10474250006

METHOD BLANK: 3272920 Matrix: Water

Associated Lab Samples: 10474250001, 10474250002, 10474250003, 10474250004, 10474250005, 10474250006

Blank Reporting

Parameter Units Result Limit Analyzed Qualifiers

Chloride mg/L ND 2.0 05/13/19 09:00

LABORATORY CONTROL SAMPLE: 3272921

Spike LCS LCS % Rec Parameter Units Conc. Result % Rec Limits Qualifiers Chloride mg/L 15 15.3 102 90-110

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 3272922 3272923

MS MSD 10473720001 Spike Spike MS MSD MS MSD % Rec Max Parameter Units Result Conc. Conc. Result Result % Rec % Rec Limits **RPD** RPD Qual Chloride 80-120 20 18.8 15 15 30.8 31.6 80 85 3 mg/L

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 3272924 3272925

MS MSD 10474250001 MS MSD MS MSD Spike Spike % Rec Max RPD Qual Parameter Units Result Conc. Conc. Result Result % Rec % Rec Limits RPD Chloride 118 15 15 137 138 121 129 80-120 20 M6 mg/L

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.

(612)607-1700



QUALIFIERS

Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to dilution of the sample aliquot.

ND - Not Detected at or above adjusted reporting limit.

TNTC - Too Numerous To Count

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PQL - Practical Quantitation Limit.

RL - Reporting Limit - The lowest concentration value that meets project requirements for quantitative data with known precision and bias for a specific analyte in a specific matrix.

S - Surrogate

1,2-Diphenylhydrazine decomposes to and cannot be separated from Azobenzene using Method 8270. The result for each analyte is a combined concentration.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.


ANALYTE QUALIFIERS

Date: 05/17/2019 03:46 PM

FS The sample was filtered in the laboratory prior to analysis.

H1 Analysis conducted outside the recognized method holding time.

M6 Matrix spike and Matrix spike duplicate recovery not evaluated against control limits due to sample dilution.





QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project: 0102B0412.000 City of Baxter

Pace Project No.: 10474250

Date: 05/17/2019 03:46 PM

Lab ID	Sample ID	QC Batch Method	QC Batch	Analytical Method	Analytical Batch
10474250001	 Lugo #1	SM 9222B	605113	SM 9222B	605117
10474250002	Lugo #2	SM 9222B	605113	SM 9222B	605117
10474250003	Katzenberger #1	SM 9222B	605113	SM 9222B	605117
10474250004	Katzenberger #2	SM 9222B	605113	SM 9222B	605117
10474250005	Bolt #1	SM 9222B	605113	SM 9222B	605117
10474250006	Bolt #2	SM 9222B	605113	SM 9222B	605117
10474250001	Lugo #1	EPA 353.2	605133		
10474250002	Lugo #2	EPA 353.2	605133		
10474250003	Katzenberger #1	EPA 353.2	605133		
10474250004	Katzenberger #2	EPA 353.2	605133		
10474250005	Bolt #1	EPA 353.2	605133		
10474250006	Bolt #2	EPA 353.2	605133		
10474250001	Lugo #1	SM 4500-CI E	605370		
10474250002	Lugo #2	SM 4500-CI E	605370		
10474250003	Katzenberger #1	SM 4500-CI E	605370		
10474250004	Katzenberger #2	SM 4500-CI E	605370		
10474250005	Bolt #1	SM 4500-CI E	605370		
10474250006	Bolt #2	SM 4500-CI E	605370		

CHAIN-OF-CUSTODY RECORD

			: :			: 1										_ :			. <u>.</u>			:	:		:
Distribution: White – Accompanies Shipment; Pink – Project File; Yellow – Laboratory		Relinquished by: (Signature)	120	Relinquished by: (Signature)									Rolf # 2	14 1/08	Katrembered #7	5	Luas # 2	Luge#1	SAMPLE DESCRIPTION	SAMPLERS: (Print)	SAMPLERS: (Signature)	1		NOLTING	WIDSETH SMITH
anies Shipment	_	e)		9)					:		:		5/9/19		0	5/4/14	5/9/16	5/4/14	DATE	Michael Bay	ent	Baxter	PROJECT NAME	1	
; Pink – P		Date /	S/A/IA	Date /				: :			:		1455	15:54	11.47	11:41	10.15	9:34	TIME	£ +		2			ALEXANDRIA 320.762.8149
roject Fil		Time	1741	/ Time					.: :						: '	_			COMP				Virginden		::
le; Yellow	M	Receiv		Received by:						, i			3	7	X	7	ठ	7	GRAB	.::			11		BEMIDJI 218.444.1859
/ – Laboratory	Lyca	Received for Laboratory by: (Signature)		ed by: (Signature)				. :		:.			tho	theo	HrO	410	the	Hib	SAMPLE MATERIAL			:	icas EA	Wic	
: 	8	y by: (Signature)			: : :								4	2	4	4		2			CON- TAINERS	유	NUMBER	WidsethSmithNolting.com ENGIN	BRAINERD/ BAXTER 218.829.5117
No. 6228	Stole	Dat		Reli	·		1						ß	X	×	3	7	Z	01	,			ANALYSES REQUEST	ng.com	CROOKSTON 218.281.6522
150.k	15 9%)	Date / Time		Relinquished	_				:		.:		7	5	7	X	7	3	Children Tel	Pride	<u> </u>	: .	SES	ENGIN	STON .6522
			.:	by: (Signature)				. :					-4	8	X	<u>ス</u>	\	X	I da /	(5				EERING	EAS 218
6/0180412.000	Brian	Report To:		nature)						. 1-:			-					<u>.</u> :		e s	m/e			1	EAST GRAND FORKS 218.773.1185
111						.:				: .			-	1.									(2)	ARCHITECTURE	
000	10>>			Date / Time								. :	ماص	205	2	23	200	(3)		Pose pro	10474250		₩0#:	RE LAND SUR	FOREST LAKE 651.464.3130
				Received by: (Signature)										:						Pare prosled 22189	REMARKS		WO#:10474250	VEYING ENVIRONMI	1 12 12 12 12 12 12 12 12 12 12 12 12 12
		_		nature)			:																50	ENTAL SERVICES	ROCHESTER 1 507.292.8743

Pace Analytical*

Document Name: Sample Condition Upon Receipt Form

Document No.: F-MN-L-213-rev.27 Document Revised: 05Apr2019 Page 1 of 1

Issuing Authority: Pace Minnesota Quality Office

Sample Condition Upon Receipt Client Name:			Pr	oject #:	MO	#:1	04742	250	:
Courier: Fed Ex JUPS		SPS	——. □Clie	nt !	PM:	0E0	Due Da	e: 05/	17/19
Tracking Number: Pace SpeeDee	ہے ∏در		ial See Ex		CLIE	NT: Wid	seth		
Custody Seal on Cooler/Box Present?	No	Se	als Intact	:?	∏No	Biolog	sical Tissue Froze	n? Nes	
Packing Material: Bubble Wrap Bubble Ba	ags [None	□Oth	ner:			Temp Blank		
Thermometer: T1(0461) T2(1336) T3(0459) T4(0254) T5(0048)		Type of		Wet 🔲	Blue	None	□Dry □Me	elted	
Note: Each West Virginia Sample must have temp take					· .				
Temp should be above freezing to 6°C Cooler Temp Res	ad w/ten	np blani	k:).4	·	⁰C	Average Correct	-	See Exceptions
Correction Factor: Cooler Temp Correcte	d w/tem	ıp blank	<u>::(</u>).(<i>(</i>		oc	(no temp blan	k only): _°C	L
USDA Regulated Soil: (\(\sum \text{V}/A\), water sample/Other:)	Date/Init	ials of Pe	erson Exam	ining Contents:		<u> </u>
Did samples originate in a quarantine zone within the Unit	ed States	: AL, AR,	_	A, Did sam	ples origir	nate from a f	oreign source (inte		including
ID, LA. MS, NC, NM, NY, OK, OR, SC, TN, TX or VA (check m	aps)? [Yes	No	Hawaii a	and Puerto	o Rico)?	☐Yes ☐]No	_
If Yes to either question, fill out a F	regulate	a Soli Ci	neckiist (i	F-IVIN-Q-338)	and incl			vork.	
				 _			COMMENTS:		
Chain of Custody Present and Filled Out? Chain of Custody Relinquished?	/ Ves	□No		1.					
	Yes	□No		2.					
Sampler Name and/or Signature on COC? Samples Arrived within Hold Time?	Yes Yes	No	N/A	3.	 -		· · · · · · · · · · · · · · · · · · ·	_	
Short Hold Time Analysis (<72 hr)?	Hes			5.	l Coliform	Пнрс □16	tal Coliform/E coli	BOD/cBOD	Hex Chrome
Rush Turn Around Time Requested?	Yes	No		6.	iuity [INI	trate Mitth	te Orthophos C	tner	
Sufficient Volume?	Yes			7.					
Correct Containers Used?	Yes			8.			·		<u> </u>
-Pace Containers Used?	Dires	. □No		8.					•
Containers Intact?	Dygs	□No		9.					
Field Filtered Volume Received for Dissolved Tests?	∏Yes							_ = = = = = = = = = = = = = = = = = = =	
Is sufficient information available to reconcile the samples	Tes	No	□N/A				lissolved container Container Below:	·? []Yes	
to the COC? Matrix: Water Soil Oil Other	Tes	□No		002	NIE 10, DE	zen		escn	F See Exception
All containers needing acid/base preservation have been				12. Sample	2110)f	3 All	empl-	<u></u>	
checked?	Yes	□No	□N/A	12. Sample	# > 1. 1.	•	•		
All containers needing preservation are found to be in compliance with EPA recommendation? (HNO ₃ , H ₂ SO ₄ , <2pH, NaOH >9 Sulfide, NaOH>12 Cyanide)	Ves	□No	□N/A		NaOH	□нис	03 DH2504	[] 	linc Acetate
Exceptions: VOA, Coliform, TOC/DOC Oil and Grease, DRO/8015 (water) and Dioxin/PFAS	∐Yes	∏No		Positive for Chlorine? Res. Chlorin			H Paper Lot#	, 	See Exception -14 Strip
			أسير	13.		·			See Exception
Headspace in VOA Vials (greater than 6mm)? Trip Blank Present?	Yes	□No	N/A			·			
Trip Blank Custody Seals Present?	□Yes □Yes	□No □No	DN/A	14. Pace T	rip Blank	Lot # (if pur	rchased):		
CLIENT NOTIFICATION/RESOLUTION			 . '	7 .			Data Required?	Yes	No
Person Contacted: Comments/Resolution:				Date/Time	e:				
							<u> </u>		
Project Manager Review: Ougue	mi()	din	ole		Date:		5/10/19		
Note: Whenever there is a discrepancy affecting North Langina chold, incorrect preservative, out of temp, incorrect containers).	complianc	e sample	s, a copy c	of this form wil	be sent t	to the North	Carolina DEHNR Ce	rtification (Office (i.e out of

Labeled by: _

ATTACHMENT C Soil Boring Logs

	WIDS SMIT NOLT	ETH H ING	Engine Archite Survey Enviro	ecture	WidsethSmithNoiting.com	Proj Proj	ect Number: ect Name: ect Location: ng Number:	O102B0412.0 City of Baxter Baxter, MN Lugo #1	Unsewered Areas E	A 1203.83
Sample # and Time	Sample Type	Recovery (inches)	Moisture	PID Readings (ppm)	U.S.C.S. Symbol	Depth (feet)	Start Date: Completion Date	5/9/2019 : 5/9/2019		9:00 9:40
Sam	Sar T	Rec (inc	Moj	Rea (P)	U.S Syr	g #	Completion Date		scription	9.40
9:16	CS	31	Da	0.4	FILL	_	Fill- Silty Sand, L		wn, Highly Organic	
					SP	-	COARSE ALLUN	/IUM Loose Br	own, FINE GRAINED) SAND
			M	1.1	O.		Some Mottling P		own, i me ordane	
9:21	CS	46	М	1.2	SP	5				
			W				Trace Gravel Pre	esent		
							Turns Dark Brow	n in Color		
			М	1.2						
								End of Boring	@ 8'	
						10				_
						<u> </u>				
						L 15				
						15				_
						20				
						25				
						<u> </u>				
						30				
	Water	Level Measu	ırments (feet	<u> </u>					© 2007 WIDSETH	H SMITH NOLTING
Date	Time	Sample Depth	Casing Depth	Cave-in Depth	Water Level	Drilli	ng Method:	Geoprobe		
5/9/2019	9:34	4-8	8	8	1.8	Bacl	xfill Method:	Bentonite		
						Field	d Representative:	MB		

	WIDS SMIT NOLT	SETH H TING	Engine Archite Survey Enviro	ecture	WidsethSmithNoiting.com	Proj Proj	ect Number: ect Name: ect Location: ng Number:	0102B0412.00 City of Baxter Baxter, MN Lugo #2	Unsewered Areas E Surface Elevation:	A 1202.70
Sample # and Time	Sample Type	Recovery (inches)	Moisture	PID Readings (ppm)	U.S.C.S. Symbol	Depth (feet)	Start Date: Completion Date	5/9/2019 : 5/9/2019		9:40 10:20
9:49	CS	44	Da	1.1	FILL SP		-	oose, Dark Bro	wn, Highly Organic own, FINE GRAINED	
			М	1.3	OI .			DIUM COARSE	GRAINED SAND	
9:56	cs	48	W	1.4	SP	5	Turns Gray/Tan i			
				1.5			Turn Tan in Colo			
						10		End of Boring	@ 8'	
						15				
										_
						20				
						25				
						30				
	Wate	r Level Meas	urments (feet)					© 2007 WIDSFTI	H SMITH NOLTING
Date	Time	Sample Depth	Casing Depth	Cave-in Depth	Water Level	Drilli	ng Method:	Geoprobe		-
5/9/2019	10:15	4-8	8	8	1.1	Back	xfill Method:	Bentonite		
						Field	l Representative:	MB		

	WIDS SMIT NOLT	ETH H ING	Engine Archite Survey Enviro	ecture	WidsethSmithNoiting.com	Proje Proje	ect Number: ect Name: ect Location: ng Number:	0102B0412.00 City of Baxter Baxter, MN Katz #1	Unsewered Areas E	A 1209.13
Sample # and Time	Sample Type	Recovery (inches)	Moisture	PID Readings (ppm)	U.S.C.S. Symbol	Depth (feet)	Start Date: Completion Date			10:30 11:20
10:51	CS	40	Da	0.4	FILL SP				wn, Highly Organic ed/Tan, FINE GRAIN	ED SAND
10:55	CS	44	Da	0.8 1.1	SP	5	Turns Tan in Col	or		
11:00	CS	42	Da w	1.4	SP		Turns Brown in C Gravel Present	Color, Some Me	dium Grained Sand a	and Trace
				1.2		20		End of Boring	@ 12'	
	Water		urments (feet	·					© 2007 WIDSETH	H SMITH NOLTING
Date 5/9/2019	Time 11:11	Sample Depth 8-12	Casing Depth	Cave-in Depth	Water Level 8.7		ng Method:	Geoprobe		
2.2.23.13							fill Method: I Representative:	Bentonite MB		

	WIDS SMIT NOLT	ETH H ING	Engine Archite Survey Enviro	ecture	WidsethSmithNoiting.com	Proje Proje	ect Number: ect Name: ect Location: ng Number:	0102B0412.00 City of Baxter Baxter, MN Katz #2	Unsewered Areas EA Surface Elevation:	1207.41
Sample # and Time	Sample Type	Recovery (inches)	Moisture	PID Readings (ppm)	U.S.C.S. Symbol	ا∵ب خا	Start Date: Completion Date			11:25 12:00
11:31	CS	38	Da	0.9	FILL SP			Loose, Dark Brow	wn, Highly Organic ed/Tan, FINE GRAINEI	D SAND
11:34	CS	40	Da M W	1.7	SP	5	Turns Tan in Co	lor		_
11:39	CS	44	W	1.4	SP	10	Turns Tan/Brow	n in Color With 1	race Mottling Present	
						20		End of Boring	@ 12"	
		Level Measu	urments (feet) Cave-in	Water	5	a a Marth	0	© 2007 WIDSETH S	MITH NOLTING
Date 5/9/2019	Time 11:47	Depth 8-12	Depth 12	Depth 12	Level 7.05		ng Method: cfill Method:	Geoprobe Bentonite		
							Representative:			

	WIDS SMIT NOLT	ETH H ING	Engine Archite Survey Enviro	ecture	WidsethSmithNoiting.com	P P	roje	ect Number: 0102B0412.000 ect Name: City of Baxter Unsewered Areas EA ect Location: Baxter, MN ng Number: Bolt #1 Surface Elevation: 1195.41
Sample # and Time	Sample Type	Recovery (inches)	Moisture	PID Readings (ppm)	U.S.C.S. Symbol	Depth (foot)	(leer)	Start Date: 5/9/2019 Time: 13:00 Completion Date: 5/9/2019 Time: 14:00
		_						Description
13:13	CS	42	Da	1.3	FILL SP			FILL- Silty Sand, Loose, Dark Brown, Highly Organic
					36	_		COARSE ALLUVIUM, Loose, Brown, FINE GRAINED SAND
				1.1				
13:15	CS	46	Da	1.2	SP		5	Turns Tan in Color
13.13	00		Ба	1.2	OI.		٦	
								Becomes Fine to Medium Coarse Grained
				1.4				
13:20	CS	47	Da	1.6	SP	-		
10.20		.,	Bu	1.0	O.		10	
								Trace Mottling Present
				1.7				
13:24	CS	46	Da	1.8	SP	 		
10.21			Du	1.0	O.			
							15	Becomes Coarse Grained With Some Gravel
				1.7		_		
13:30	CS	42	Da	1.5	SP			Becomes Fine to Medium Coarse Grained With Trace Gravel
10.00			2			┌,	_	
		,	W					Becomes Light Tan
				1.6			20	<u> </u>
13:38	CS	40	W	1.3	SP			Becomes Medium Coarse With Some Gravel
								Turns Rust Red in Color
				1.3				
							25	End of Boring @ 24'
		ļ					30	
	Water	Level Measu	ırments (feet)				© 2007 WIDSETH SMITH NOLTING
Date	Time	Sample Depth	Casing Depth	Cave-in Depth	Water Level	D	rilli	ng Method: Geoprobe
5/9/2019	14:00	20-24	24	24	18.3	В	ack	xfill Method: Bentonite
								I Dannasantativas - MD
							eid	Representative: MB

	WIDS SMIT NOLT	H ING	Engine Archite Survey Enviro	ecture ing nmental	WidsethSmithNolting.com	Proj Proj	ect Name: ect Location:	0102B0412.0 City of Baxter Baxter, MN Bolt #2	Unsewered Areas E Surface Elevation:	A 1191.30
Sample # and Time	Sample Type	Recovery (inches)	Moisture	PID Readings (ppm)	U.S.C.S. Symbol	Depth (feet)	Start Date: Completion Date:	5/9/2019 5/9/2019		14:05 15:00
San	Saı Ty	Rec (inc	Moi	Rea (Pl	U.S Syr	و م	Completion Date.		scription	13.00
14:13	CS	41	Da	1	FILL	,	FILL- Silty Sand, L		rown, Highly Organic	
				•	SP				own, FINE GRAINE	
								- , ,	, -	
				1.3			Turn Tan in Color			
14:16	CS	46	Da	0.7	SP	5				
							Becomes Fine to N	Medium Coars	e Grained, Trace Gra	avel Present
				1						
14:24	CS	41	Da	1.3	SP					
						10				
				1.2						
14:29	CS	49	Da	1.2	SP					
						15				
				1.7			No Gravel Present	t		
14:35	CS	38	Da	0.9	SP		Turns Light Tan in	Color		
				1.8		20				
14:49	CS	41	Da	1.2	SP					
			W	1.1						
						25		End of Boring	@ 24'	
						30				
						_				
	\\/ato	r Level Meası	irments (fect	<u> </u>					© 2007 WIDSET	H SMITH NOLTING
		Sample	Casing	Cave-in	Water				⊕ 2007 WIDSEII	Janitti NOLTING
Date	Time	Depth	Depth	Depth	Level	Drilli 	ng Method:	Geoprobe		
5/9/2019	14:55	20-24	24	24	23.7	Bacl	fill Method:	Bentonite		
						F:_!	I Donroscotation	MD		
						rieid	Representative:	IVID		

Widseth Smith Nolting SOIL BORING LOG DESCRIPTIVE TERMINOLOGY

GRAIN SIZE								
Soil Fraction	Particle Size	U.S. Standard Sieve						
Boulders	Larger than 300mm	Larger than 12"						
Cobbles	75mm to 33mm	3" to 12"						
Gravel: Coarse	19mm to 75mm	3/4" to 3"						
Fine	4.75mm to 19mm	#4 to 3/4"						
Sand: Coarse	2.00mm to 4.75mm	#10 to #4						
Medium	0.425mm to 2.00 mm	#40 to #10						
Fine	0.075mm to 0.425mm	#200 to #40						
Silt	0.005mm to 0.075mm	Smaller than #200						
Clay	Smaller than 0.005mm	Smaller than #200						

RELATIVE PROPORTIONS							
<u>Term</u>	Range	<u>Term</u>	Range				
Trace	0-5%	Some	10-30%				
Little	5-10%	With	30-50%				

DENSITY	BLOW COUNTS	CONSISTENCY
<u>Term</u>	N - Value	<u>Term</u>
Very Loose	0-4	Very Soft
Loose	5-8	Soft
Medium Dense	9-15	Firm
Dense	16-30	Hard
Very Dense	Over 30	Very Hard


Standard Penetration Test (N-Value): Blows per foot of a 140 pound hammer falling 30 inches on a 2-inch O.D. Split Barrel Sampler

SOIL MOISTURE								
Dry	Dry DR Powdery, absence of moisture							
Damp	Da	Residual moisture on soil grains						
Moist	М	Below saturation						
Wet	w	Saturated, visible free water						

SOIL STRUCTURE	
Fracture	Cracks of fissures
Seam	Up to 1/8" thick
Lamination	1/8" to 1/2" thick
Lense	½" to 6" thick stratum
Layer	Over 6" thick stratum
Varved	Alternating colored laminations of clay, silt, and/or fine-grained sand

DRILLING AND SAMPLING		
CS	Continuous Sampling	
RC	Rock Coring; Size AQ,BQ,NQ,PQ,PQ	
RB	Rock Bit	
CW	Clear Water	
DM	Drilling Mud	
MR	Mud Rotary	
AR	Air Rotary	
СТ	Cable Tool	
HSA	Hollow Stem Auger	
FA	Flight Auger	
НА	Hand Auger	
SS	2" Diameter Split-Barrel Sample	
2ST	2" Diameter Thin-Walled Tube Sample	
3ST	3" Diameter Thin-Walled Tube Sample	
AS	Auger Sample	
CTC	Cable Tool Cuttings	
ws	Washed Sample	
NR	No Recovery	
NMR	No Measurement Recorded	
1M	Jetting Water	
ND	Not Detected Above Background	
NS	Not Sampled	

GEOLOGIC TERMS		
Coarse Alluvium	Sand and/or gravel sediments deposited by water action	
Fine Alluvium	Silt and/or clay sediment deposited by water action	
Mixed Alluvium	Mixture of Coarse and Fine Alluvium	
Till	Unsorted sediments deposited directly by glacial ice	
Colluvium	Talus and slope deposits	
Eolian or Loess	Sediments deposited by wind action	
Lacustrine	Sediments deposited at the bottom of a lake or pond	
Peat	Organic material deposited in swamp or marsh	
Fill	Sediments placed by man	



Water level


Note: Water level measurements shown on the boring logs represent conditions at the time indicated and may not reflect static levels, especially in cohesive soils.

Widseth Smith Nolting


DESCRIPTION AND IDENTIFICATION OF SOILS

ASTM Designation D 2488-93 (Visual-Manual Procedure)


Flow Chart for Identifyng Inorganic Fine-Grained Soil (50% or more fines)



Flow Chart for Identifying Organic Fine-Grained Soil (50% or more fines)



Flow Chart for Identifying Coarse-Grained Soils (less than 50% fines)



	Criteria for Describing Dry Strength
Description	<u>Criteria</u>
None	The dry speciment crumbles into powder with mere pressure of handling
Low	The dry speciment crumbles into powder with some finger pressure
Medium	The dry specimen breaks into pieces or crumbles with considerable finger pressure
High	The dry specimen cannot be broken with finger pressure. Specimen will break into pieces between thumb and a hard surface
Very High	The dry specimen cannot be broken between the thumb and a hard surface

Criteria for Describing Dilatancy			Criteria for Describing Toughness
Description	<u>Criteria</u>	Description	<u>Criteria</u>
None	No visible change in the specimen	Low	Only slight pressure is required to roll the thread near the plastic limit. The thread and the lump are weak and soft
Slow	Water appears slowly on the surface of the specimen during shaking and does not disappear or disappears slowly upon squeezing	Medium	Medium pressure is required to roll the thread to near the plastic limit. The thread and the lump have medium stiffness
Rapid	Water appears quickly on the surface of the specimer during shaking and disappears quickly upon squeezing	High	Considerable pressure is required to roll the thread to near the plastic limit. The thread and the lump have very high stiffness

Identification of Inorganic Fine-Grained Soils from Manual Tests			
Soil Symbol	Dry Strength	Dilatancy	Toughness
ML	None to low	Slow to rapid	Low or thread cannot be formed
CL	Medium to high	None to slow	Medium
MH	Low to medium	None to slow	Low to medium
CH	High to very high	None	High

Widseth Smith Nolting

CLASSIFICATION OF SOIL FOR ENGINEERING PURPOSES

ASTM Designation: D 2487-93

(Based on Unified Soil Classification System)

COARSE-GRAINED SOILS (50% or more larger than No. 200 sieve size)

GRAVELS 50% or more of coarse fraction larger than No. 4 sieve	Clean Gravels (Less than 5% fines) GW Well-graded gravels, gravel-sand mixtures, little or no fines Clean Gravels (Less than 5% fines) GP Poorly graded gravels, gravel-sand mixtures, little or no fines Gravels with fines (Greater than 12% fines)	
	GM Silty gravels, gravel-sand-silt mixtures	
	Gravels with fines (Greater than 12% fines)	
	GC Clayey gravels, gravel-sand-clay mixtures	
	Clean sands (Less than 5% fines)	
SANDS 50% or more of	SW Well-graded sands, gravelly sands, little or no fines	
coarse fraction	Clean sands (Less than 5% fines)	
smaller	SP Poorly graded sands, gravelly sands, little or no	
than No. 4	fines	
sieve	Sand with Fines (Greater than 12% fines)	
	SM Silty sands, sand-silt mixtures	
	SM Silty sands, sand-silt mixtures Sand with Fines (Greater than 12% fines)	

FINE-GRAINED SOILS		
(50% or more smaller than No. 200 Sieve)		

SILTS AND CLAYS Liquid limit less than 50%	ML Inorganic silts and very fine sands, rock flour, silty or clayey fine sands, or clayey silts with slight plasticility
	CL Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
	OL Organic silts & organic silty clays of low
SILTS AND CLAYS Liquid Limit 50% or More	MH Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts
	CH Inorganic clays of high plasticity, fat clays
	OH Organic clays of medium to high plasticity, organic silts

HIGHLY ORGANIC SOILS		
PEAT Primarily Organic Matter	Fibric Peat > 67% fibers PT Hemic Peat 33%-67% fibers Sapric Peat < 33% fibers	

LABORATORY CLASSIFICATION CRITERIA

GW \underline{D}_{60} greater than or equal to 4; $\underline{(D_{30})^2}$ between 1 and 3 $D_{10} \times D_{60}$

Where D_{60} , D_{30} , D_{10} are the particle diameters corresponding to 60%, 30%,10% passing on the cumulative particle-size distribution curve.

GP Not meeting all gradation requirements for GW

GM *Atterberg limits below "A" *Above "A" line with P.I. line or P.I. less than 4 between 4 and 7 are borderline cases requiring use of dual

GC *Atterberg limits above "A" line with P.I. greater than 7 symbols GC-GM

*For fine-grained fraction

SW \underline{D}_{60} greater than or equal to 6; $(\underline{D}_{30})^2$ between 1 and 3 $D_{10} x D_{60}$

Where D₆₀,D₃₀,D₁₀ are the particle diameters corresponding to 60%, 30%,10% passing on the cumulative particle-size distribution curve.

SP Not meeting all gradation requirements for SW

SM *Atterberg limits below "A" line or P.I. less than 4

*Above "A" line with P.I. between 4 and 7 are borderline cases requiring use of dual symbols SC-SM

SC *Atterberg limits above "A" with P.I. greater than 7

*For fine-grained fraction

Gravels with 5 to 12% fines require dual symbols:

GW-GM well-graded gravel with silt GW-GC well-graded gravel with clay GP-GM poorly graded gravel with silt GP-GC poorly graded gravel with clay

Sands with 5 to 12% fines require dual symbols:

SW-SM well-graded sand with silt SW-SC well-graded sand with clay SP-SM poorly graded sand with silt SP-SC poorly graded sand with clay

